GloveSpec · SPECIFICATION SHEET

GlassGuard High-Cut Glove

Cut-Resistant Gloves · S-XXL · MOQ 600 pairs · 35-40 days

Range	Cut-Resistant Gloves
Construction	UHMWPE, steel fiber and nylon, 13 gauge
Coating / palm	PU palm coating with uncoated back
Sizes	S-XXL
Weight	72 g/pair
Palm stack	1.6 mm
MOQ	600 pairs
Lead time	35-40 days
Packing	Individual polybag, 120 pairs per carton
Customisation	Custom gauge, cuff colour and private label
Quoted standards	EN 388: 2016 · EN 420
HS code (indicative)	6116.10 (coated knitted gloves)
Test report	Issued per production batch by a notified body, on request.

Typical use

Glass Handling · Metal Handling

Before you commit

Send with the enquiry	Model code or this data sheet, quantity, size ratio, destination port, artwork and any label standard.
Documents on request	Business licence, factory audit summary, batch test report for the model you order, export records with buyer details redacted.
Sampling terms	Counter-samples in 3–5 days on stock models; sample cost credited against the bulk order.

Specifications are indicative and confirmed against the approved sample before bulk production. Cold and cut ratings are measured per production batch; the report that ships with your order states the measured values for that batch.

GloveSpec · Jiaxiang, Shandong, China · sales reply within one business day · Full line card: GloveSpec.com/downloads/GloveSpec-Line-Card.pdf