GloveSpec · SPECIFICATION SHEET

OilGrip Full-Coated Nitrile Glove

Nitrile-Coated Gloves · S-XXL · MOQ 500 pairs · 30-35 days

Range	Nitrile-Coated Gloves
Construction	HPPE, polyester and steel fiber, 13 gauge
Coating / palm	Full nitrile coating to the knitted cuff
Sizes	S-XXL
Weight	66 g/pair
Palm stack	1.5 mm
MOQ	500 pairs
Lead time	30-35 days
Packing	12 pairs per polybag, 120 pairs per carton
Customisation	Custom colour, cuff label and carton artwork
Quoted standards	EN 388: 2016 · EN 420
HS code (indicative)	6116.10 (coated knitted gloves)
Test report	Issued per production batch by a notified body, on request.

Typical use

Oily Conditions · Automotive

Before you commit

Send with the enquiry	Model code or this data sheet, quantity, size ratio, destination port, artwork and any label standard.
Documents on request	Business licence, factory audit summary, batch test report for the model you order, export records with buyer details redacted.
Sampling terms	Counter-samples in 3–5 days on stock models; sample cost credited against the bulk order.

Specifications are indicative and confirmed against the approved sample before bulk production. Cold and cut ratings are measured per production batch; the report that ships with your order states the measured values for that batch.

GloveSpec · Jiaxiang, Shandong, China · sales reply within one business day · Full line card: GloveSpec.com/downloads/GloveSpec-Line-Card.pdf